



Quick assembly instructions
for DS / AKU locator

DS locate

PASSENGER / DELIVERY CAR

1.

Open the hood of the car and find the battery. To mount the locator to the battery, use the wrench that is included in the kit.



2.

Wipe the mounting area on the battery with the included disinfectant wipe to clean the place before sticking the locating device.



3.

Connect the DS/AKU locator to the battery clamps.



4.

Remember to connect red wire to the plus on the car battery.



5.

Stick the DS/AKU device to the battery with the double-sided tape on the bottom of the device.



6.

Correct installation is confirmed by a green LED.



The correctness of the device installation is signaled by LED diodes, the statuses of which are indicated below:

- The LEDs are off: no power to the device.
- The "Status LED" flashes about once a second and the "Navigate LED" is lit continuously - the device is communicating with the system, but is not locating.
- The "Status LED" is lit steadily and the "Navigate LED" flashes approximately once every second - the device has acquired a track of but is unable to communicate with the system.
- The Status LED "and the" Navigate LED "flash approximately once per second - the device is working properly.
- Status LED "and" Navigate LED "flash very fast - device is updating its software.



In order to verify the correctness of the device installation and receiving alerts from e-TOLL system, log in to the **DS Locate** application. You can download it for free from the **Google Play** or **AppStore**.



A video of the assembly of the device can be found here:
bit.ly/Montaz-AKU

Regulations for the provision of location services based on the DS Locate system and the rental or sale of devices available at www.datasystem.pl

Data System Group

ul. abpa A. Baraniaka 88 B
61-131 Poznań | Poland
t. + 48 61 62 63 000
biuro@datasystem.pl

Tech Support

Mon. - Fri. 8.00 - 18.00
Sat. 8.00 - 15.00
pomoc.techniczna@datasystem.pl

www.datasystem.pl